

## 3-TERMINAL 1A POSITIVE ADJUSTABLE REGULATOR

The KIA317F/FP/PI/S is adjustable 3-terminal positive voltage regulator capable of supplying in excess of 1.5A over a 1.25V to 37V output range. This is exceptionally easy to use and require only two external resistors to set the output voltage. Further, both line and load regulation are better than standard fixed regulators.

### FEATURES


- Adjustable output between 1.25V and 37V
- Guaranteed 1.5A output current
- Line regulation typically 0.001%/V
- Load regulation typically 0.1%
- 80dB ripple rejection (with Cadj)
- Internal thermal overload protection
- Internal short-circuit current limiting
- Output transistor safe-area compensation

### MAXIMUM RATINGS (Ta=25 °C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Input-Output Voltage Differential		$V_{IN}$	40	V
Output Current		$I_{OUT}$	1.5	A
Power Dissipation (No Heatsink)	F	$P_D$	1.3	W
	FP		2.0	
	PI		2.0	
	S (Note)		1.0	
Operating Temperature		$T_{opr}$	-30 85	
Storage Temperature		$T_{stg}$	-65 150	
Lead Temperature		$T_{lead}$	230	

Note) : Package Mounted on FR-4 PCB 36 × 18 × 1.5mm.  
mounting pad for the GND Lead min. 6cm<sup>2</sup>.

### BLOCK DIAGRAM



# KIA317F/FP/PI/S

## ELECTRICAL CHARACTERISTICS (Ta=25 °C)


(Vin-Vo=5V, Io=0.5A, 0 ≤ Tj ≤ 125 °C, I\_MAX=1.5A, unless otherwise specified.)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT	
Line Regulation	Vo(Line)	Ta=25 °C, Io=10mA	3V Vin-Vout 40V	-	0.01	0.04	% / V
		Ta=0 ~ 125 °C, Io=10mA		-	0.02	0.07	
Load Regulation	Vo(Load)	Ta=25 °C	10mA Iout I_MAX	-	0.1	0.5	%
		Ta=0 ~ 125 °C		-	0.3	1.5	
Adjustable Pin Current	IAdj		-	50	100	μA	
Adjustable Pin Current Change	IAdj	10mA Io I_MAX, 3V Vin-Vout 40V	-	0.2	5	μA	
Reference Voltage	Vref	10mA Io I_MAX, 3V Vin-Vout 40V, P P_MAX	1.20	1.25	1.30	V	
Temperature Stability	ST_T	T_Min Tj T_Max	-	1	-	%	
Minimum Load Current to Maintain Regulation	Io(MIN)	(Vin-Vout)=40V	-	3.5	10	mA	
Current Limit	Io(MAX)	(Vin-Vout) 15V, P P_MAX	1.5	2.2	3.4	A	
		(Vin-Vout) 40V, P P_MAX, Ta=25 °C	0.15	0.4	-	A	
Output Noise Voltage	V_NO	Ta=25 °C, 10Hz ≤ f ≤ 10kHz, % of Vout	-	0.0003	-	%	
Ripple Rejection Ratio	RR	Vo=10V, f=120Hz	-	65	-	dB	
		C_Adj=10μF	66	80	-		
Long Term Stability	ST	Ta=25 °C for end point measurement, 1000 Hr	-	0.3	1	%	

Note : Load and line regulation are specified at constant junction temperature.

Change in Vo due to heating effects must be taken into account separately. Pulse testing with low duty is used.

## TYPICAL APPLICATION (PROGRAMMABLE REGULATOR)




Ci is required when regulator is located an appreciable distance from power supply filter.

Co is not needed for stability, however, in the range of 1μF to 100μF of aluminum or tantalum electrolytic are commonly used to provide improved output impedance and rejection of transients.


Since IAdj is controlled to less than 100μA, the error associated with this term is negligible in most applications.

# KIA317F/FP/PI/S


Load Regulation




Current Limit




Adjustment Current




Dropout Voltage




Temperature Stability




Minimum Operating Current




### Ripple Rejection




### Ripple Rejection




### Ripple Rejection




### Output Impedance



### Line Transient Response




### Line Transient Response




# KIA317F/FP/PI/S


Power Dissipation-2 (DPAK)




Power Dissipation-3 (D<sup>2</sup>PAK)



Power Dissipation-1 (TO-220IS)



Power Dissipation-4 (SOT-223)



# KIA317F/FP/PI/S

