

## BAT46

### FEATURES :


- For general purpose applications.
- This diode features very low turn-on voltage and fast switching. This device is protected by a PN junction guard ring against excessive voltage, such as electrostatic discharges
- This diode is also available in the MiniMELF case with type designations LL46.
- Pb / RoHS Free

### MECHANICAL DATA :

**Case:** DO-35 Glass Case

**Weight:** approx. 0.13g

## SCHOTTKY BARRIER DIODE



### Maximum Ratings and Thermal Characteristics (Rating at 25 °C ambient temperature unless otherwise specified.)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	100	V
Continuous Forward Current	$I_F$	150 <sup>(1)</sup>	mA
Repetitive Peak Forward Current at $t_p < 1s$ ,	$I_{FRM}$	350 <sup>(1)</sup>	mA
Forward Surge Current at $t_p < 10ms$ ,	$I_{FSM}$	750 <sup>(1)</sup>	mA
Power Dissipation , $T_a = 65\text{ }^\circ\text{C}$	$P_D$	150 <sup>(1)</sup>	mW
Thermal Resistance Junction to Ambient Air	$R_{\theta JA}$	0.3 <sup>(1)</sup>	$^\circ\text{C/W}$
Junction Temperature	$T_J$	125	$^\circ\text{C}$
Ambient Operating Temperature Range	$T_a$	-65 to + 125	$^\circ\text{C}$
Storage temperature range	$T_s$	-65 to + 150	$^\circ\text{C}$


Note: (1) Valid provided that leads at a distance of 4mm from case are kept at ambient temperature.

### Electrical Characteristics ( $T_J = 25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\ \mu\text{A}$ (pulsed)	100	-	-	V
Reverse Current	$I_R$	$V_R = 10\ \text{V}$	-	-	0.8	$\mu\text{A}$
Pulse Test $t_p < 300\ \mu\text{s}$ , $\delta < 2\%$		$V_R = 50\ \text{V}$	-	-	2.0	
		$V_R = 75\ \text{V}$	-	-	5.0	
Forward Voltage	$V_F$	$I_F = 10\ \text{mA}$	-	-	0.45	V
Pulse Test $t_p < 300\ \mu\text{s}$ , $\delta < 2\%$		$I_F = 250\ \text{mA}$	-	-	1.00	
Diode Capacitance	$C_d$	$V_R = 1\ \text{V}$ , $f = 1\ \text{MHz}$	-	6	-	pF

### RATING AND CHARACTERISTIC CURVES ( BAT46 )

**Admissible Power Dissipation vs. Ambient Temperature**



**Typical Forward Characteristics**



**Typical Reverse Characteristics**

